


2006/07



DIRECTORY

LED PRO 3

HOSHI	Recessed 1W LED luminaire, perfect for a starry sky and many other decorative light effects	4
KIDO	Recessed 1W LED luminaire with 10°, 30° and 60° beam angle	5
KAN	Recessed 1W LED luminaire with decorative white POM reflector	6
NAU	Pivoting recessed 1W LED luminaire with 60° beam angle and diffuser	7
TOGARI	Recessed 3W LED luminaire with 10°, 30° and 60° beam angle	8
NAMI 1	Recessed 1W LED wall washer with 1 radiation pattern	9
NAMI 2	Recessed 1W LED wall washer with 2 radiation patterns	10
NAMI 3	Recessed 1W LED wall washer with 3 radiation patterns	11
NAMI 6	Recessed 1W LED wall washer with 5 radiation patterns	12
KIYONA	Surface-mounted 1W LED luminaire, fully adjustable with 10°, 30° and 60° beam angle	13
TECHNICAL	LED driver	14
VISIONS	Customized luminaires	15

SEQUENCE 17


GAMMA 51	Surface-mounted luminaire for 12V and 120-230V MR16	18
DELTA 51	Surface-mounted luminaire for 12V and 120-230V MR16, fully adjustable	20
GAMMA 111	Surface-mounted luminaire for 12V / AR111 and 120-230V / R111	21
Technical	Transformers	23

MONOS 25

CUBE	Surface-mounted luminaire with socket G 9 /120-240V and handcrafted glass	26
------	---	----

LED

PRO



LED PRO

We redesigned and improved our LED line for professional requirements; the result is our new outstanding LED PRO series solving even the most demanding of tasks.

LED PRO advantage

- Available in chrome, matte chrome and bronze.
- All luminaires have the same mounting system and mounting diameters.
- High quality long lasting materials and finishing.
- Bright light output because of optimized lenses and reflectors.

LED PRO is flexible and designed for customizing. Choose your own finish and LED color for corporate identity or just to match with an interior design.

For our LED PRO luminaires, we exclusive use the world's brightest LEDs offering up to 120 lumens per single source and are available in a variety of configurations.

PRO

HOSHI



Recessed star light for indoor, white POM reflector - perfect for a starry sky and many other decorative light effects

LED: 1 W Power LED

Power Supply: LED-converter 350 mA, constant current (not included)

Wiring: In series

Rating: Class II

Lamp life: white 70% at 50,000 hrs





HOSHI LED Recessed Luminaire, fixed
1 W Power LED, 110° beam angle

Item No	Finish	LED Color
07-1030-04	chrome	soft white 3300K
07-1030-05	matte chrome	soft white 3300K
07-1030-06	bronze*	soft white 3300K
07-1035-04	chrome	cool white 5500K
07-1035-05	matte chrome	cool white 5500K
07-1035-06	bronze*	cool white 5500K
07-1030-x4	chrome	
07-1030-x5	matte chrome	
07-1030-x6	bronze*	

*Color variations may occur due to the special plating process

x=1 red
x=2 green
x=3 blue
x=4 amber

Please replace the placeholder "x" in the Item number above with the number of the desired LED color





Recessed spot light for indoor, acrylic lens with 10° and 30° beam angle or optical glass lens with 60° beam angle.

LED: 1 W Power LED

Power Supply: LED-converter 350 mA, constant current (not included)

Wiring: In series

Rating: Class II

Lamp life: white 70% at 50,000 hrs

KIDO 10° LED Recessed Luminaire, fixed
1 W Power LED, 10° beam angle



Item No	Finish	LED Color
07-0010-04	chrome	soft white 3300K
07-0010-05	matte chrome	soft white 3300K
07-0010-06	bronze*	soft white 3300K
07-0015-04	chrome	cool white 5500K
07-0015-05	matte chrome	cool white 5500K
07-0015-06	bronze*	cool white 5500K
07-0010-x4	chrome	
07-0010-x5	matte chrome	
07-0010-x6	bronze*	

KIDO 30° LED Recessed Luminaire, fixed
1 W Power LED, 30° beam angle

Item No	Finish	LED Color
07-0020-04	chrome	soft white 3300K
07-0020-05	matte chrome	soft white 3300K
07-0020-06	bronze*	soft white 3300K
07-0025-04	chrome	cool white 5500K
07-0025-05	matte chrome	cool white 5500K
07-0025-06	bronze*	cool white 5500K
07-0020-x4	chrome	
07-0020-x5	matte chrome	
07-0020-x6	bronze*	

KIDO GL LED Recessed Luminaire, fixed, glass lens 60° beam angle
1 W Power LED

Item No	Finish	LED Color
07-0020-04	chrome	soft white 3300K
07-0020-05	matte chrome	soft white 3300K
07-0020-06	bronze*	soft white 3300K
07-0025-04	chrome	cool white 5500K
07-0025-05	matte chrome	cool white 5500K
07-0025-06	bronze*	cool white 5500K
07-0020-x4	chrome	
07-0020-x5	matte chrome	
07-0020-x6	bronze*	



*Color variations may occur due to the special plating process

x=1 red
x=2 green
x=3 blue
x=4 amber

Please replace the placeholder "x" in the Item number above with the number of the desired LED color

KAN



Recessed spot light for indoor, white POM reflector,
 LED: 1 W Power LED
 Power Supply: LED-converter 350 mA, constant current (not included)
 Wiring: In series
 Rating: Class II
 Lamplife: white 70% at 50,000 hrs





KAN LED Recessed Luminaire, fixed
 1 W Power LED

Item No	Finish	LED Color
07-0030-04	chrome	soft white 3300K
07-0030-05	matte chrome	soft white 3300K
07-0030-06	bronze*	soft white 3300K
07-0035-04	chrome	cool white 5500K
07-0035-05	matte chrome	cool white 5500K
07-0035-06	bronze*	cool white 5500K
07-0030-x4	chrome	
07-0030-x5	matte chrome	
07-0030-x6	bronze*	

*Color variations may occur due to the special plating process

x=1 red
 x=2 green
 x=3 blue
 x=4 amber

Please replace the placeholder "x" in the Item number above with the number of the desired LED color



NAU



Recessed spot light for indoor, 60° chrome reflector and diffuser
 LED: 1 W Power LED
 Power Supply: LED-converter 350 mA, constant current (not included)
 Wiring: In series
 Rating: Class II
 Lamplife: white 70% at 50,000 hrs





**NAU
LED** Recessed Luminaire, pivoting
 1 W Power LED

Item No	Finish	LED Color
07-0040-04	chrome	soft white 3300K
07-0040-05	matte chrome	soft white 3300K
07-0040-06	bronze*	soft white 3300K
07-0045-04	chrome	cool white 5500K
07-0045-05	matte chrome	cool white 5500K
07-0045-06	bronze*	cool white 5500K
07-0040-x4	chrome	
07-0040-x5	matte chrome	
07-0040-x6	bronze*	

*Color variations may occur due to the special plating process

x=1 red
 x=2 green
 x=3 blue
 x=4 amber

Please replace the placeholder "x" in the Item number above with the number of the desired LED color



TOGARI



Recessed spot light for indoor, acrylic lens with 10° and 30° beam angle or optical glass lens with 60° beam angle.

LED: 3 W Power LED

Power Supply: LED-converter 700 mA, constant current (not included)

Wiring: In series

Rating: Class II

Lamp life: white 70% at 50,000 hrs

TOGARI 10° LED Recessed Luminaire, fixed, acrylic lens 10° beam angle
3 W Power LED




Item No	Finish	LED Color
07-1055-04	chrome	neutral white 4000K
07-1055-05	matte chrome	neutral white 4000K
07-1055-06	bronze*	neutral white 4000K
07-1050-04	chrome	cool white 5500K
07-1050-05	matte chrome	cool white 5500K
07-1050-06	bronze*	cool white 5500K
07-1050-x4	chrome	
07-1050-x5	matte chrome	
07-1050-x6	bronze*	

TOGARI 30° LED Recessed Luminaire, fixed, acrylic lens 30° beam angle
3 W Power LED

Item No	Finish	LED Color
07-2055-04	chrome	neutral white 4000K
07-2055-05	matte chrome	neutral white 4000K
07-2055-06	bronze*	neutral white 4000K
07-2050-04	chrome	cool white 5500K
07-2050-05	matte chrome	cool white 5500K
07-2050-06	bronze*	cool white 5500K
07-2050-x4	chrome	
07-2050-x5	matte chrome	
07-2050-x6	bronze*	

TOGARI GL LED Recessed Luminaire, fixed, glass lens 60° beam angle
3 W Power LED

Item No	Finish	LED Color
07-0055-04	chrome	neutral white 4000K
07-0055-05	matte chrome	neutral white 4000K
07-0055-06	bronze*	neutral white 4000K
07-0050-04	chrome	cool white 5500K
07-0050-05	matte chrome	cool white 5500K
07-0050-06	bronze*	cool white 5500K
07-0050-x4	chrome	
07-0050-x5	matte chrome	
07-0050-x6	bronze*	



*Color variations may occur due to the special plating process

x=1 red
x=2 green
x=3 blue
x=4 amber

Please replace the placeholder "x" in the Item number above with the number of the desired LED color

NAMI



Recessed wall washer for indoor, available in different radiation patterns,
 LED: 1 W Power LED Side Emitting
 Power Supply: LED-converter 350 mA, constant current (not included)
 Wiring: In series
 Rating: Class II
 Lamplife: white 70% at 50,000 hrs






NAMI 1 LED Recessed Luminaire, fixed
 1 W Power LED Side Emitting

Item No	Finish	LED Color
07-0065-04	chrome	neutral white 4300K
07-0065-05	matte chrome	neutral white 4300K
07-0065-06	bronze*	neutral white 4300K
07-0060-04	chrome	cool white 5500K
07-0060-05	matte chrome	cool white 5500K
07-0060-06	bronze*	cool white 5500K
07-0060-x4	chrome	
07-0060-x5	matte chrome	
07-0060-x6	bronze*	

*Color variations may occur due to the special plating process

x=1 red
 x=2 green
 x=3 blue
 x=4 amber

Please replace the placeholder "x" in the Item number above with the number of the desired LED color



NAMI



Recessed wall washer for indoor, available in different radiation patterns,
 LED: 1 W Power LED Side Emitting
 Power Supply: LED-converter 350 mA, constant current (not included)
 Wiring: In series
 Rating: Class II
 Lamplife: white 70% at 50,000 hrs






NAMI 2 LED Recessed Luminaire, fixed
 1 W Power LED Side Emitting

Item No	Finish	LED Color
07-1065-04	chrome	neutral white 4300K
07-1065-05	matte chrome	neutral white 4300K
07-1065-06	bronze*	neutral white 4300K
07-1060-04	chrome	cool white 5500K
07-1060-05	matte chrome	cool white 5500K
07-1060-06	bronze*	cool white 5500K
07-1060-x4	chrome	
07-1060-x5	matte chrome	
07-1060-x6	bronze*	

*Color variations may occur due to the special plating process

x=1 red
 x=2 green
 x=3 blue
 x=4 amber

Please replace the placeholder "x" in the Item number above with the number of the desired LED color



NAMI



Recessed wall washer for indoor, available in different radiation patterns,
 LED: 1 W Power LED Side Emitting
 Power Supply: LED-converter 350 mA, constant current (not included)
 Wiring: In series
 Rating: Class II
 Lamplife: white 70% at 50,000 hrs






NAMI 3 LED Recessed Luminaire, fixed
 1 W Power LED Side Emitting

Item No	Finish	LED Color
07-0075-04	chrome	neutral white 4300K
07-0075-05	matte chrome	neutral white 4300K
07-0075-06	bronze*	neutral white 4300K
07-0070-04	chrome	cool white 5500K
07-0070-05	matte chrome	cool white 5500K
07-0070-06	bronze*	cool white 5500K
07-0070-x4	chrome	
07-0070-x5	matte chrome	
07-0070-x6	bronze*	


*Color variations may occur due to the special plating process

x=1 red
 x=2 green
 x=3 blue
 x=4 amber

Please replace the placeholder "x" in the Item number above with the number of the desired LED color



NAMI



Recessed wall washer for indoor, available in different radiation patterns,
 LED: 1 W Power LED Side Emitting
 Power Supply: LED-converter 350 mA, constant current (not included)
 Wiring: In series
 Rating: Class II
 Lamplife: white 70% at 50,000 hrs






**NAMI 6
LED** Recessed Luminaire, fixed
 1 W Power LED Side Emitting

Item No	Finish	LED Color
07-0085-04	chrome	neutral white 4300K
07-0085-05	matte chrome	neutral white 4300K
07-0085-06	bronze*	neutral white 4300K
07-0080-04	chrome	cool white 5500K
07-0080-05	matte chrome	cool white 5500K
07-0080-06	bronze*	cool white 5500K
07-0080-x4	chrome	
07-0080-x5	matte chrome	
07-0080-x6	bronze*	

*Color variations may occur due to the special plating process

x=1 red
 x=2 green
 x=3 blue
 x=4 amber

Please replace the placeholder "x" in the Item number above with the number of the desired LED color



KIYONA



Surface mounted spot light for indoor, fully adjustable, acrylic lens with 10° and 30° beam angle or optical glass lens with 60° beam angle.

LED: 3 W Power LED

Power Supply: LED-converter 700 mA, constant current (not included)

Wiring: In series

Rating: Class II

Lamp life: white 70% at 50,000 hrs

KIYONA 10° LED Surface mounted Luminaire, fully adjustable, 3 W Power LED, acrylic lens 10° beam angle

Item No	Finish	LED Color
07-0090-04	chrome	neutral white 4000K
07-0090-05	matte chrome	neutral white 4000K
07-0090-06	bronze*	neutral white 4000K
07-0095-04	chrome	cool white 5500K
07-0095-05	matte chrome	cool white 5500K
07-0095-06	bronze*	cool white 5500K
07-0090-x4	chrome	
07-0090-x5	matte chrome	
07-0090-x6	bronze*	

KIYONA 30° LED Surface mounted Luminaire, fully adjustable, 3 W Power LED, acrylic lens 30° beam angle

Item No	Finish	LED Color
07-0100-04	chrome	neutral white 4000K
07-0100-05	matte chrome	neutral white 4000K
07-0100-06	bronze*	neutral white 4000K
07-0105-04	chrome	cool white 5500K
07-0105-05	matte chrome	cool white 5500K
07-0105-06	bronze*	cool white 5500K
07-0100-x4	chrome	
07-0100-x5	matte chrome	
07-0100-x6	bronze*	


KIYONA GL LED Surface mounted Luminaire, fully adjustable, 3 W Power LED, glass lens 60° beam angle

Item No	Finish	LED Color
07-0130-04	chrome	neutral white 4000K
07-0130-05	matte chrome	neutral white 4000K
07-0130-06	bronze*	neutral white 4000K
07-0135-04	chrome	cool white 5500K
07-0135-05	matte chrome	cool white 5500K
07-0135-06	bronze*	cool white 5500K
07-0130-x4	chrome	
07-0130-x5	matte chrome	
07-0130-x6	bronze*	

*Color variations may occur due to the special plating process

x=1 red
x=2 green
x=3 blue
x=4 amber

Please replace the placeholder "x" in the Item number above with the number of the desired LED color





LED 4 W 350 mA LED Electronic converter / driver
1-3 LED 1 W in series, 350 mA constant current

Load 1-4 VA
Input 100-240 V 50/60 Hz
Output 2-14 V

Protection Electronic internal resettable short circuit protection.
Thermal protection and overload regulation.

Dimensions
Plastic L 1.77" x W 1.77" x H 0.98" (45 x 45 x 25 mm)

Item No **Case**
901004350U Plastic, waterproof potting



LED 10 W 350 mA LED Electronic converter / driver
1-8 LED 1 W in series, 350 mA constant current

Load 9-18 VA
Input 95-265 V 50/60 Hz
Output 2-28 V

Protection Electronic internal resettable short circuit protection.
Thermal protection and overload regulation.

Dimensions
Plastic L 3.93" x W 1.57" x H 1.10" (100 x 40 x 28 mm)
Aluminum L 3.38" x W 1.37" x H 1.06" (86 x 35 x 27 mm)

Item No **Case**
901010350 Plastic
901010350PU Aluminum, waterproof potting



LED 18 W 700 mA LED Electronic converter / driver
3-6 LED 3 W in series, 700 mA constant current

Load 1-10 VA
Input 85-277 V 50/60 Hz
Output 10-24 V

Protection Electronic internal resettable short circuit protection.
Thermal protection and overload regulation.



Dimensions
Plastic L 6.22" x W 1.77" x H 1.26" (158 x 45 x 32 mm)
Aluminum L 5.24" x W 1.57" x H 1.20" (133 x 40 x 30.5 mm)

Item No **Case**
901018700 Plastic
901018700P Aluminum, waterproof potting



Flexibility

Customize any of the lights to your personal preferences to match your specific environments. Our goal is to provide you with the perfect matching lighting conditions for your individual scenarios. Contact us for any special request that you might have.



SEQUENCE

by kania



Featuring a highly sophisticated and uniform design, Sequence is a lighting collection capable of satisfying the most demanding lighting needs. The range of sizes, and the varied lighting effects that can be achieved using different lighting technologies, make sequence highly flexible in use. The fixtures are designed for indoor applications or for protected outdoor locations.

Naturally, all lights are UL-standard tested*, easy to install and reliable in operation. Only the highest grades of stainless steel and aluminum are used, and great care is taken in the finish. *HID pending

As ever, the design by Martin Kania features classic, clean lines. It makes no concessions to the short-lived fashions of the moment. In this respect, sequence is in keeping with our company philosophy – superb, adaptable lighting and quality light fittings. Rather than dominating the architecture or interior design, they present them to their best advantage.

GAMMA 51



Surface-mounted luminaire for indoor, fixed
 Socket G 5,3 for MR-16 (12 V)
 Socket GU 10 for MR-16 (120-230 V)
 Socket GX 10 for ES-50.
 The luminaires are available in aluminum similar to RAL 9006 or solid stainless steel.



GAMMA 51 Surface-mounted luminaire, fixed
12 V max 50 W, MR-16 / QR-51 (G 5.3)

Item No **Finish**
 05-2020-01 aluminum similar to RAL 9006
 05-2020-10 solid stainless steel



Use with transformer (not included)

GAMMA 51 Surface-mounted luminaire, fixed
120 V max 50 W, MR-16 / QR-51 (G 10) 120-240 V

Item No **Finish**
 05-2125-01 aluminum similar to RAL 9006
 05-2125-10 solid stainless steel




GAMMA 51 Surface-mounted luminaire, fixed
HID max 35 W, ES-50 (GX10)

Item No **Finish**
 05-2136-01 aluminum similar to RAL 9006
 05-2136-10 solid stainless steel



Use with electronic metal halide ballast (not included)





DELTA 51



Surface-mounted luminaire for indoor, fully adjustable

Socket G 5,3 for MR-16 (12 V)

Socket GU 10 for MR-16 (120-230 V)

Socket GX 10 for ES-50

The luminaires are available in aluminum similar to RAL 9006 or solid stainless steel.



DELTA 51 Surface-mounted luminaire, fully adjustable
12 V max 50 W, MR 16 / QR-51 (G 5.3)

Item No	Finish
05-2130-01	aluminum similar to RAL 9006
05-2130-10	solid stainless steel



Use with transformer (not included)

DELTA 51 Surface-mounted luminaire, fully adjustable
120 V max 50 W, MR 16 / QR-51 (G 10) 120-240 V

Item No	Finish
05-2135-01	aluminum similar to RAL 9006
05-2135-10	solid stainless steel




DELTA 51 Surface-mounted luminaire, fully adjustable
HID max 35 W, ES 50 (GX10)

Item No	Finish
05-2026-01	aluminum similar to RAL 9006
05-2026-10	solid stainless steel



ETL pending

Use with electronic metal halide ballast (not included)



GAMMA 111



Surface-mounted luminaire for indoor, fixed
 Socket G 53 for AR-111 / QR-111 (12 V)
 Socket GU 10 for R-111 (120-230 V)
 Socket GX 8.5 for CDM-R 111
 The luminaires are available in aluminum similar to RAL 9006 or solid stainless steel.



GAMMA 111 Surface-mounted luminaire, fixed
12 V max 100 W, AR-111 / QR-111 (G 53)

Item No **Finish**
 05-2050-01 aluminum similar to RAL 9006
 05-2050-10 solid stainless steel



Use with transformer (not included)

GAMMA 111 Surface-mounted luminaire, fixed
120 V max 75 W, R-111 (G 10) 120-240 V

Item No **Finish**
 05-2055-01 aluminum similar to RAL 9006
 05-2055-10 solid stainless steel




GAMMA 111 Surface-mounted luminaire, fixed
HID max 70 W, CDM-R 111 (GX 8.5)

Item No **Finish**
 05-2056-01 aluminum similar to RAL 9006
 05-2056-10 solid stainless steel



Use with electronic metal halide ballast (not included)







Glass Plate for Gamma 111 (Luminaire not included)

Item No	Dimensions	Finish
05-2900-01	10" x 10" / 250 x 250 mm	aluminum
05-2900-10	10" x 10" / 250 x 250 mm	stainless steel



LET-105

LET-75 **Electronic Transformer**
No image, finish similar to LET-105

Load	75W max
Input	120 V / 60 Hz
Output	11.7 V
Dimensions	L 2.09" x W 1.30" x H 0.79" (53 x 33 x 20 mm)

Item No	Case
901075000	Standard, aluminum, waterproof potting
901075005	Bottom Feed, aluminum, waterproof potting



LET-151

LET-105 **Electronic Transformer**

Load	105 W max.
Input	120 V / 60 Hz
Output	11.5 V
Dimensions	L 3.15" x W 1.34" x H 0.87" (80 x 34 x 22 mm)

Item No	Case
901105012	Standard, aluminum, waterproof potting

LET-151 **Electronic Transformer**

Load	150 W max.
Input	120 V / 60 Hz
Output	11.8 V
Dimensions	L 3.39" x W 1.38" x H 1.06" (86 x 35 x 27 mm)

Item No	Case
901151010	Standard, aluminum, waterproof potting




LET-301

LET-301 **Electronic Transformer**


Load	300 W max.
Input	120 V / 60 Hz
Output	11.5 V
Dimensions	Outside diameter 3.70 / Inside diameter 0.39 x H 1.34 (94 / 10 x 34 mm)

Item No	Case
901301000	Standard, aluminum, waterproof potting

All transformers have electronic internal resettable short circuit protection, thermal protection and overload regulation.




M O N O S



CUBE





Surface-mounted luminaire for indoor, fixed
 Socket G 9 /120-240V)
 The luminaires are available in stainless steel with hand crafted glass
 and can be mounted parallel or diagonal to the ceiling plate.



CUBE Surface-mounted luminaire, fixed
120 V max 2 A, T4 (G 9) 120-240 V

Item No	Finish	Glass Color
05-2055-01	stainless steel	white
05-2055-10	stainless steel	amber
05-2055-01	stainless steel	dark red
05-2055-10	stainless steel	blue





kania

LIGHTING SYSTEMS

3330 Sheehan Drive
Land O Lakes, FL 34638
Phone 813-949-7862
Fax 813-949-7348
E-Mail info@kania.us
Web www.kania.us